

Sets

Inserts


Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters


Specific applications and Sets



Specific applications and Sets

Specific applications

02 3/4.00
Spot facing milling cutters



Page F.02 CC.. 0602..
CC.. 09T3..

0624.21
Chamfering cutters



Page F.04 TC.. 1102..

0724.21
Chamfering cutters




Page F.04 TC.. 1102..

1220.21
Face and square 90°




Page F.06 AP.. 1003..

2220.21
Face and square 90°



Page F.06 AP.. 1003..

1135.01
Convexe milling cutters



Page F.08 ADMW-C 1503..

1235.01
Concave milling cutters



Page F.10 ADMW-R 1503..

1235.07
Concave milling cutters




Page F.10 ADMW-R 1503..

16 3/4.2 1/2
Chamfering cutters



Page F.12 TC.. 1102..
TC.. 16T3..

1725. 2/7
Chamfering cutters



Page F.14 ADMW-R 1503..

1735. 2/7
Chamfering cutters




Page F.15 ADMW-C 1503..

1744. 2/7
Chamfering cutters




Page F.16 SC.. 1204..

3314.0 1/2
Multi-function




Page F.18 CCKT 0602..
CCKT 1204..

9614.61
Back draft spot facing



Page F.20 CC.. 0602..
CC.. 09T3..

9624.61
Back draft countersink



Page F.21 CC.. 0602..
TC.. 1102..

Sets

SET MAXICUT
Spot facing milling cutters



Page F.03 CC.. 0602..
CC.. 09T3..

SET MINICUT
Chamfering cutters



Page F.05 TC.. 1102..

SET 1220
Face and square 90°



Page F.07 AP.. 1003..

SET 1135
Convexe milling cutters



Page F.09 ADMW-C 1503..

SET 1235
Concave milling cutters



Page F.11 ADMW-R 1503..

SET MULTICUT
Chamfering cutters



Page F.13 TC.. 1102..
TC.. 16T3..

SET CCKT
Multi-function



Page F.19 CCKT 0602..
CCKT 1204..

Specific applications
and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and
adaptors

Specific applications and sets

For more information see page:

Contents: F.02
Sets: F.03
Tools: F.10

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and Sets






Characteristics:

Spot facing milling cutters for flat screw heads.

The inserts are fixed by Torx screw that allow a good chip evacuation and easy use.

Applications:

Flat countersink.



02¹₃4.00

Ref.			D	d	a	L	L2	M	Insert size	
0214.00.011	1		11	12	4	85	15	M6	CC.. 0602..	0,100
0214.00.014	1		14	12	5	85	19	M8	CC.. 0602..	0,100
0234.00.017	1		17	16	5	95	30	M10	CC.. 09T3..	0,125
0234.00.019	1		19	16	5	95	32	M12	CC.. 09T3..	0,125
0234.00.022	1		22	16	6	95	32	M14	CC.. 09T3..	0,150
0234.00.025	1		25	16	8	95	32	M16	CC.. 09T3..	0,150

Ref.			
0214.00.011		1425	5507
0214.00.014		1425	5507
0234.00.017		1440	5515
0234.00.019		1440	5515
0234.00.022		1440	5515
0234.00.025		1440	5515

Ref.	CC..			Positive 7° clearance - 80° rhombic inserts.
	l	s	d	
CC.. 0602..	6,45	2,38	6,35	For more information see page: A.12
CC.. 09T3..	9,65	3,97	9,52	
	CCGT-AL	CCKT	CCMW	






Characteristics:

Spot facing milling cutters for flat screw heads.

The inserts are fixed by Torx screw that allow a good chip evacuation and easy use.

Applications:


Flat countersink.



SET MAXICUT

Ref.			D	d	a	L	L2	M	Insert size	
0214.00.011	1		11	12	4	85	15	M6	CC.. 0602..	0,800
0214.00.014	1		14	12	5	85	19	M8	CC.. 0602..	
0234.00.017	1		17	16	5	95	30	M10	CC.. 09T3..	
0234.00.019	1		19	16	5	95	32	M12	CC.. 09T3..	
0234.00.022	1		22	16	6	95	32	M14	CC.. 09T3..	
0234.00.025	1		25	16	8	95	32	M16	CC.. 09T3..	


Ref.		
0214.00.011	1425	5507
0214.00.014	1425	5507
0234.00.017	1440	5515
0234.00.019	1440	5515
0234.00.022	1440	5515
0234.00.025	1440	5515



Ref.	CC..	l	s	d	Positive 7° clearance - 80° rhombic inserts.
	CC.. 0602..	6,45	2,38	6,35	
CC.. 09T3..	9,65	3,97	9,52		

CCGT-AL	CCKT	CCMW			

For more information see page: A.12



Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and Sets






Characteristics:

Countersink milling cutter for specific operations. The insert is fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:

This general milling cutters work well on steels, alloyed steels, stainless steels and refractors. This general milling cutter for diversified manufacture is recommended for small conventional milling machines and machining centers.



0624.21

Ref.			D1	D	L	L2	d	Insert size	
0624.21.016	1		1,2	16	70	24	12	TC.. 1102..	0,100
0624.21.021	2		8,5	21	90	30	20	TC.. 1102..	0,150




Ref.	0624.21.016		1425		5507
	0624.21.021		1425		5507

Characteristics:

Countersink milling cutter for specific operations. The insert is fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:

This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors. This general milling cutter for diversified manufacture is recommended for small conventional milling machines and machining centers.



0724.21

Ref.			D1	D	L	L2	d	Insert size	
0724.21.016	1		5,4	16	70	24	12	TC.. 1102..	0,100
0724.21.026	2		15,8	26	90	30	20	TC.. 1102..	0,170

Ref.	0724.21.016		1425		5507
	0724.21.026		1425		5507

	TC..			Positive 7° clearance - Triangular inserts.
	Ref.	l	s	
	TC.. 1102..	11,00	2,38	6,35
	TCGT-AL	TCMT-39	TCMW	

For more information see page: A.20






Characteristics:

Countersink milling cutter for specific operations. The insert is fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:


This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors. This general milling cutter for diversified manufacture is recommended for small conventional milling machines and machining centers.



SET MINICUT

Ref.			D1	D	L	L2	d	Insert size	
0624.21.016	1		1,2	16	70	24	12	TC.. 1102..	0,600
	2		8,5	21	90	30	20	TC.. 1102..	
0724.21.016	1		5,4	16	70	24	12	TC.. 1102..	
	2		15,8	26	90	30	20	TC.. 1102..	

Ref.				
0624.21.016	1		1425	5507
	2		1425	5507
0724.21.016	1		1425	5507
	2		1425	5507



	TC..			Positive 7° clearance - Triangular inserts.	
	Ref.	TC.. 1102..	l	s	d
			11,00	2,38	6,35
	TCGT-AL	TCMT-39	TCMW		

For more information see page: A.20

Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and sets




Characteristics:

This positive milling cutter with an exact angle of 90° uses very strong inserts allowing deep passes and high feed per teeth. The insert is fixed by a Torx screw that allows a good chip evacuation and an easy use.

Milling cutter equipped with short Weldon shank.

Applications:

This face and square (angle 90°), slot and side milling cutter works well on steels, alloyed steels, stainless steels, refractory casts and aluminium alloys. This general milling cutter for diversified manufacture is recommended for conventional milling machines and machining centers.



1220.21			D	d	a	L2	L	Insert size	
Ref.	1220.21.012	1	12	16	10	25	85	AP.. 1003..	0,100
	1220.21.016	2	16	16	10	25	85	AP.. 1003..	0,150
	1220.21.020	3	20	20	10	30	90	AP.. 1003..	0,150

Ref.	1220.21.012		1425	5507
	1220.21.016		1425	5507
	1220.21.020		1425	5507


Characteristics:

This super positive drill milling cutter with an exact angle of 90° uses strong inserts allowing deep passes. The insert is fixed by a Torx screw that allows a good chip evacuation and an easy use.

Milling cutter equipped with short Weldon shank.

Applications:

This drill milling cutter, works well on steels, alloyed steels, stainless steels, refractory casts and aluminium alloys. This general milling cutter for diversified manufacture is recommended for conventional milling machines and machining centers.



2220.21			D	d	a	L2	L	Insert size	
Ref.	2220.21.020	1+1	20	20	19	35	90	AP.. 1003..	0,150

Ref.	2220.21.020		1425	5507
------	-------------	--	------	------

		AP..	l	s	d	Positive 11° clearance - Rectangular inserts.
Ref.	AP.. 1003..		9,52	3,18	6,35	
For more information see page: A.11						
	APHT-AL	APKT				




Characteristics:

This positive milling cutter with an exact angle of 90° uses very strong inserts allowing deep passes and high feed per teeth. The insert is fixed by a Torx screw that allows a good chip evacuation and an easy use. Milling cutter equipped with short Weldon shank.

Applications:


This face and square (angle 90°), slot and side milling cutter works well on steels, alloyed steels, stainless steels, refractory casts and aluminium alloys. This general milling cutter for diversified manufacture is recommended for conventional milling machines and machining centers.



SET 1220

Ref.			D	d	a	L2	L	Insert size	
1220.21.012	1		12	16	10	25	85	AP.. 1003..	0,650
	2		16	16	10	25	85	AP.. 1003..	
	3		20	20	10	30	90	AP.. 1003..	
	2220.21.020	1+1	20	20	19	35	90	AP.. 1003..	

Ref.		
1220.21.012	1425	5507
1220.21.016	1425	5507
1220.21.020	1425	5507
2220.21.020	1425	5507



	AP..		l	s	d	Positive 11° clearance - Rectangular insert.
	Ref.	AP.. 1003..	9,52	3,18	6,35	
	APHT-AL	APKT				

For more information see page: A.11

Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and Sets






Characteristics:

Convex milling cutters for specific applications.

The inserts are fixed by Torx screw that allow a good chip evacuation and easy use.

Applications:

This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors.




1135.01

Ref.		d	D	L	L2	r _{min}	r _{max}	Insert size	
1135.01.01610	1	16	16	120	35	1,0	3,0	ADMW-C 1503R1.0 / 3.0	0,200
1135.01.01635	1	16	16	120	35	3,5	6,0	ADMW-C 1503R3.5 / 6.0	0,200

Ref.		
1135.01.01610	1440	5515
1135.01.01635	1440	5515

ADMW-C					Positive 11° clearance - Rectangular inserts.		
Ref.	r	s	d				
ADMW 1503R1.0-C	1.00	3,18	9,52				
ADMW 1503R1.5-C	1.50	3,18	9,52				
ADMW 1503R2.0-C	2.00	3,18	9,52				
ADMW 1503R2.5-C	2.50	3,18	9,52				
ADMW 1503R3.0-C	3.00	3,18	9,52				
ADMW 1503R3.5-C	3.50	3,18	9,52				
ADMW 1503R4.0-C	4.00	3,18	9,52				
ADMW 1503R4.5-C	4.50	3,18	9,52				
ADMW 1503R5.0-C	5.00	3,18	9,52				
ADMW 1503R6.0-C	6.00	3,18	9,52				
	R1.0-C	R1.5-C	R2.0-C	R2.5-C	R3.0-C	R3.5-C	R4.0-C



For more information see page: A.10






Characteristics:

Convex milling cutters for specific applications.

The inserts are fixed by Torx screw that allow a good chip evacuation and easy use.

Applications:

This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors.



SET 1135


Ref.			d	D	L	L2	r _{min}	r _{max}	Insert size	
1135.01.01610	1		16	16	120	35	1,0	3,0	ADMW-C 1503R1.0 / 3.0	0,550
1135.01.01635	1		16	16	120	35	3,5	6,0	ADMW-C 1503R3.5 / 6.0	

Ref.				
1135.01.01610			1440	5515
1135.01.01635			1440	5515



Ref.	ADMW-C				Positive 11° clearance - Rectangular inserts.		
	r	s	d				
ADMW 1503R1.0-C	1.00	3,18	9,52				
ADMW 1503R1.5-C	1.50	3,18	9,52				
ADMW 1503R2.0-C	2.00	3,18	9,52				
ADMW 1503R2.5-C	2.50	3,18	9,52				
ADMW 1503R3.0-C	3.00	3,18	9,52				
ADMW 1503R3.5-C	3.50	3,18	9,52				
ADMW 1503R4.0-C	4.00	3,18	9,52				
ADMW 1503R4.5-C	4.50	3,18	9,52				
ADMW 1503R5.0-C	5.00	3,18	9,52				
ADMW 1503R6.0-C	6.00	3,18	9,52				
	R1.0-C	R1.5-C	R2.0-C	R2.5-C	R3.0-C	R3.5-C	R4.0-C

For more information see page: A.10



Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and Sets






Characteristics:

Concave milling cutters for specific applications.

The inserts are fixed by Torx screw that allow a good chip evacuation and easy use.

Applications:

This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors.



1235.01

Ref.		d	D	L	L2	r _{min}	r _{max}	Insert size	
1235.01.01701	1	16	17	120	30	1,0	2,5	ADMW 1503R1.0 / 2.5	0,200
1235.01.01703	1	16	17	120	30	3,0	5,0	ADMW 1503R3.0 / 5.0	0,200



Ref.	1235.01.01701	1440	5515
	1235.01.01703	1440	5515




Characteristics:

Concave milling cutters for specific applications.

The inserts are fixed by Torx screw that allow a good chip evacuation and easy use.

Applications:

This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors.



1235.07

Ref.		D	d	L	L1	r _{min}	r _{max}	Insert size	
1235.07.02201	2	22	20	120	35	1,0	2,5	ADMW 1503R1.0 / 2.5	0,320
1235.07.02203	2	22	20	120	35	3,0	5,0	ADMW 1503R3.0 / 5.0	0,530



Ref.	1235.07.02201	1440	5515
	1235.07.02203	1440	5515

ADMW-R

Ref.	r	s	d
ADMW 1503R1.0	1.0	3,18	9,52
ADMW 1503R1.5	1.5	3,18	9,52
ADMW 1503R2.0	2.0	3,18	9,52
ADMW 1503R2.5	2.5	3,18	9,52
ADMW 1503R3.0	3.0	3,18	9,52
ADMW 1503R3.5	3.5	3,18	9,52
ADMW 1503R4.0	4.0	3,18	9,52
ADMW 1503R4.5	4.5	3,18	9,52
ADMW 1503R5.0	5.0	3,18	9,52

Positive 11° clearance - Rectangular inserts

For more information see page: A.10

R4.5-R R5.0-R



R1.0-R

R1.5-R

R2.0-R

R2.5-R

R3.0-R

R3.5-R

R4.0-R






Characteristics:

Concave milling cutters for specific applications. The inserts are fixed by Torx screw that allow a good chip evacuation and easy use.

Applications:

This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors.



SET 1235


Ref.			d	D	L	L2	r _{min}	r _{max}	Insert size	
1235.01.01701	1		16	17	120	30	1,0	2,5	ADMW 1503R1.0 / 2.5	0,550
1235.01.01703	1		16	17	120	30	3,0	5,0	ADMW 1503R3.0 / 5.0	

Ref.				
1235.01.01701			1440	5515
1235.01.01703			1440	5515



Ref.	ADMW-R				Positive 11° clearance - Rectangular inserts						
	r	s	d								
ADMW 1503R1.0	1.0	3,18	9,52								
ADMW 1503R1.5	1.5	3,18	9,52								
ADMW 1503R2.0	2.0	3,18	9,52								
ADMW 1503R2.5	2.5	3,18	9,52								
ADMW 1503R3.0	3.0	3,18	9,52								
ADMW 1503R3.5	3.5	3,18	9,52								
ADMW 1503R4.0	4.0	3,18	9,52								
ADMW 1503R4.5	4.5	3,18	9,52								
ADMW 1503R5.0	5.0	3,18	9,52								

For more information see page: A.10						
	R4.5-R	R5.0-R				
R1.0-R	R1.5-R	R2.0-R	R2.5-R	R3.0-R	R3.5-R	R4.0-R



Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Specific applications and sets

For more information see page:

Contents: F.02
Sets: F.03
Tools: F.10

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and Sets






Characteristics:

Regulable chamfering milling cutter for specific operations. The insert is fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:

This chamfering milling cutter for diversified manufacture is recommended for small conventional milling machines and machining centers.



16²₃4.2¹₇

Ref.			D	L	Y	Dmin	Dmax	Insert size	
1624.21.020	1		20	100	10° - 80°	5	20	TC.. 1102..	0,250
1634.21.025	1		25	100	10° - 80°	5	23	TC.. 16T3..	0,250
1634.27.025	1		25	175	10° - 80°	5	23	TC.. 16T3..	0,500

Ref.					
1624.21.020	6921	1225	1095	5507	
1634.21.025	6926	1240	1296	5515	
1634.27.025	6926	1240	1296	5515	

	TC..				Positive 7° clearance - Triangular inserts.
	Ref.	l	s	d	
	TC.. 1102..	11,00	2,38	6,35	For more information see page: A.20
	TC.. 16T3..	16,50	3,97	9,52	
	TCGT-AL	TCMT-39	TCMW		






Characteristics:

Regulable chamfering milling cutter for specific operations. The insert is fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:


This chamfering milling cutter for diversified manufacture is recommended for small conventional milling machines and machining centers.



SET MULTICUT

Ref.			D	L	Y	Dmin	Dmax	Insert size	
1624.21.020	1	20	100	10°	5	26	TC.. 1102..	0,600	
				20°	8	27			
				30°	10	27			
				40°	13	27			
				45°	14	27			
				50°	15	27			
				60°	17	26			
				70°	19	25			
				80°	20	24			
1634.21.025	1	25	100	10°	5	32	TC.. 16T3..	0,600	
				20°	6	33			
				30°	7	34			
				40°	10	33			
				45°	11	33			
				50°	13	32			
				60°	16	31			
				70°	19	29			
				80°	23	27			

Ref.				
1624.21.020	6921	1225	1095	5507
1634.21.025	6926	1240	1296	5515



	TC..				Positive 7° clearance - Triangular inserts.
	Ref.	l	s	d	
	TC.. 1102..	11,00	2,38	6,35	
TC.. 16T3..	16,50	3,97	9,52		
TCGT-AL	TCMT-39	TCMW			

For more information see page: A.20

Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and sets






Characteristics:

Regulable concave milling cutters for specific applications. The inserts are fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:




This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors.




1725.⁰/₂₇

Ref.			D	L	L1	Dmin	Dmax	Insert size	
1725.07.025		1	25,5	104	37	26,5	33,0	ADMW-R 1503	0,250
1725.27.025		1	25,5	178	37	26,5	33,0	ADMW-R 1503	0,500

Ref.				
1725.07.025	6925		1240	1296
1725.27.025	6925		1240	1296



ADMW-R		r	s	d	Positive 11° clearance - Rectangular inserts.
Ref.					
	ADMW 1503R1.0	1.0	3,18	9,52	For more information see page: A.10
	ADMW 1503R1.5	1.5	3,18	9,52	
	ADMW 1503R2.0	2.0	3,18	9,52	
	ADMW 1503R2.5	2.5	3,18	9,52	
	ADMW 1503R3.0	3.0	3,18	9,52	
	ADMW 1503R3.5	3.5	3,18	9,52	
	ADMW 1503R4.0	4.0	3,18	9,52	
	ADMW 1503R4.5	4.5	3,18	9,52	
	ADMW 1503R5.0	5.0	3,18	9,52	








Characteristics:

Regulable convex milling cutters for specific applications.

The inserts are fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:


This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors.



1735.0₂7


Ref.			D	L	L1	Dmin	Dmax	Insert size	
1735.07.025		1	25,5	104	37	26,5	34,0	ADMW-C 1503	0,360
1735.27.025		1	25,5	178	37	26,5	34,0	ADMW-C 1503	0,650

Ref.			
1735.07.025	6935	1240	1296
1735.27.025	6935	1240	1296



Ref.	ADMW-C				Positive 15° clearance - Rectangular inserts.		
	r	s	d				
ADMW 1503R1.0-C	1.00	3,18	9,52				
ADMW 1503R1.5-C	1.50	3,18	9,52				
ADMW 1503R2.0-C	2.00	3,18	9,52				
ADMW 1503R2.5-C	2.50	3,18	9,52				
ADMW 1503R3.0-C	3.00	3,18	9,52				
ADMW 1503R3.5-C	3.50	3,18	9,52				
ADMW 1503R4.0-C	4.00	3,18	9,52				
ADMW 1503R4.5-C	4.50	3,18	9,52				
ADMW 1503R5.0-C	5.00	3,18	9,52				
ADMW 1503R6.0-C	6.00	3,18	9,52				

				R4.5-C	R5.0-C	R6.0-C
R1.0-C	R1.5-C	R2.0-C	R2.5-C	R3.0-C	R3.5-C	R4.0-C



For more information see page: A.10

Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Specific applications and sets

For more information see page:

Contents: F.02
Sets: F.03
Tools: F.10

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and Sets






Characteristics:

Regulable chamfering milling cutter for specific operations. The insert is fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:


This chamfering milling cutter for diversified manufacture is recommended for small conventional milling machines and machining centers.



1744.07

Ref.		D	L	Y	Dmin	Dmax	Insert size	
1744.07.025	1	29	101	10°	7,5	30,0	SC.. 1204..	0,250
1744.27.025	1	29	176	20°	10,0	32,0	SC.. 1204..	0,500
				30°	13,0	32,5		
				40°	16,5	33,5		
				45°	17,5	33,5		
				50°	19,0	33,5		
				60°	22,0	33,5		
				70°	24,5	32,5		
				80°	27,0	31,0		

Ref.				
1744.07.025	6944	1244	1296	5520
1744.27.025	6944	1244	1296	5520



	SC..			Positive 7° clearance - Square inserts.
	Ref.	l	s	
	SC.. 1204..	12,70	4,76	12,70
	SCGT-AL	SCMT-39	SCMW	

For more information see page: A.16



Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Specific applications and sets

For more information see page:

Contents: F.02
Sets: F.03
Tools: F.10

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters



Porcupine cutters

Specific applications and Sets



Characteristics: Multi-function center-cutting end mills.

Applications: Multiple applications - Side milling, drilling and face milling. Less time in tool changing on both-conventional and N/C machines. Easily able to machine in roughing and finishing applications because of the high rake geometry and high helix which reduce cutting forces for a smoother cut. Longer tool life may be expected because of the low cutting forces generated. Improved performance will be seen in comparison to conventional end mills and mill-drills, especially when ramp milling, drilling, contouring, helical interpolation of bores, pockets or normal profiling.



3314.0⁰₁

Ref.			D	d	L	L ₂	a	Insert size	
3314.00.012	1		12	16	100	25	5,0	CCKT 060204	0,120
3314.00.016	2		16	16	100	25	5,0	CCKT 060204 / 080308	0,160
3314.00.020	2		20	20	125	32	7,0	CCKT 080308 / 09T308	0,300
3314.00.025	2		25	25	125	40	7,6	CCKT 09T308 / 120408	0,480
3314.01.012	1		12	16	150	25	5,0	CCKT 060204	0,210
3314.01.016	2		16	16	175	25	5,0	CCKT 060204 / 080308	0,250
3314.01.020	2		20	20	175	32	7,0	CCKT 080308 / 09T308	0,400
3314.01.025	2		25	25	200	40	7,6	CCKT 09T308 / 120408	0,700



Ref.				
3314.00.012	1425	-	5507	-
3314.00.016	1425	1430	5507	5508
3314.00.020	1430	1440	5508	5515
3314.00.025	1440	1245	5515	-
3314.01.012	1425	-	5507	-
3314.01.016	1425	1430	5507	5508
3314.01.020	1430	1440	5508	5515
3314.01.025	1440	1245	5515	-

		CCKT	l	s	d	Positive 7° clearance - 80° rhombic inserts.
Ref.	CCKT 0602..		6,45	2,38	6,35	
	CCKT 0803..		8,05	3,18	7,94	
	CCKT 09T3..		9,65	4,00	9,52	
	CCKT 1204..		12,90	4,76	12,70	
For more information see page: A.12						




Characteristics: Multi-function center-cutting end mills.

Applications: Multiple applications - Side milling, drilling and face milling. Less time in tool changing on both-conventional and N/C machines. Easily able to machine in roughing and finishing applications because of the high rake geometry and high helix which reduce cutting forces for a smoother cut. Longer tool life may be expected because of the low cutting forces generated. Improved performance will be seen in comparison to conventional end mills and mill-drills, especially when ramp milling, drilling, contouring, helical interpolation of bores, pockets or normal profiling.



CCKT			D	d	L	L2	a	Insert size	
Ref.	3314.00.012	1	12	16	100	25	5,0	CCKT 060204	1,350
	3314.00.016	2	16	16	100	25	5,0	CCKT 060204 / 080308	
	3314.00.020	2	20	20	125	32	7,0	CCKT 080308 / 09T308	
	3314.00.025	2	25	25	125	40	7,6	CCKT 09T308 / 120408	
	3314.01.012	1	12	16	150	25	5,0	CCKT 060204	
	3314.01.016	2	16	16	175	25	5,0	CCKT 060204 / 080308	
	3314.01.020	2	20	20	175	32	7,0	CCKT 080308 / 09T308	
	3314.01.025	2	25	25	200	40	7,6	CCKT 09T308 / 120408	

Ref.				
3314.00.012	1425	-	5507	-
3314.00.016	1425	1430	5507	5508
3314.00.020	1430	1440	5508	5515
3314.00.025	1440	1245	5515	-
3314.01.012	1425	-	5507	-
3314.01.016	1425	1430	5507	5508
3314.01.020	1430	1440	5508	5515
3314.01.025	1440	1245	5515	-



CCKT		l	s	d	Positive 7° clearance - 80° rhombic inserts.
Ref.	CCKT 0602..	6,45	2,38	6,35	
	CCKT 0803..	8,05	3,18	7,94	
	CCKT 09T3..	9,65	4,00	9,52	
	CCKT 1204..	12,90	4,76	12,70	

CCKT					

For more information see page: A.12

Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors

Specific applications and sets

For more information see page:

Contents: F.02
Sets: F.03
Tools: F.10

Inserts

Face milling cutters

Square shoulder cutters

Slot cutters

Porcupine cutters

Specific applications and Sets






Characteristics:

Back draft spot facing milling cutters for flat screw heads.

The inserts are fixed by Torx screw that allow a good chip evacuation and easy use.

Applications:

Flat countersink.



9614.61



Spot facing mills with internal coolant.

Ref.			D	d _{min}	d	L	L ₁	L ₂	L ₃	D ₁	Insert size	
9614.61.018	1		18	10,5	20	112	62	47	40	25	CC.. 0602..	0,280
9614.61.020	1		20	13,0	20	113	63	52	45	25	CC.. 0602..	0,300
9614.61.024	1		24	15,0	20	118	68	57	50	25	CC.. 0602..	0,320
9614.61.026	1		26	17,0	20	128	78	67	60	25	CC.. 0602..	0,380
9614.61.030	1		30	19,0	20	138	88	77	70	25	CC.. 0602..	0,400
9614.61.033	1		33	21,0	20	152	102	82	75	25	CC.. 09T3..	0,430

Ref.		
9614.61.018	1425	5507
9614.61.020	1425	5507
9614.61.024	1425	5507
9614.61.026	1225	5507
9614.61.030	1225	5507
9614.61.033	1440	5515

Ref.	CC..			Positive 7° clearance - 80° rhombic inserts.
	l	s	d	
CC.. 0602..	6,45	2,38	6,35	For more information see page: A.12
CC.. 09T3..	9,65	3,97	9,52	
	CCGT-AL	CCKT	CCMW	




Characteristics:

Back draft countersink milling cutter for specific operations. The insert is fixed by Torx screw that allow a good chip evacuation and an easy use.

Applications:

This chamfering milling cutters work well on steels, alloyed steels, stainless steels and refractors. This general milling cutter for diversified manufacture is recommended for small conventional milling machines and machining centers.



9624.61



Chamfering mills with internal coolant.

Ref.			D	d _{min}	d	L	L ₁	L ₂	L ₃	D ₁	Insert size	
9624.61.015	1		15	10	20	105	55	42	35	25	CC.. 0602..	0,280
9624.61.020	1		20	14	20	110	60	47	40	25	CC.. 0602..	0,300
9624.61.023	1		23	17	20	120	70	57	50	25	TC.. 1102..	0,320
9624.61.027	1		27	21	20	140	90	77	70	25	TC.. 1102..	0,380
9624.61.031	1		31	24	20	150	100	87	80	25	TC.. 1102..	0,400

Ref.		
9624.61.015	1425	5507
9624.61.020	1425	5507
9624.61.023	1225	5507
9624.61.027	1225	5507
9624.61.031	1225	5507

Ref.	CC.. / TC..		l	s	d	CC.. Positive 7° clearance - 80° rhombic inserts. For more information see page: A.12 TC.. Positive 7° clearance - Triangular inserts. For more information see page: A.20
	CC.. 0602..		6,45	2,38	6,35	
TC.. 1102..		11,00	2,38	6,35		
	CCGT-AL	CCKT	CCMW	TCGT-AL	TCMT-39	TCMW

Specific applications and sets

Profile milling

Solid carbide

Drills

Boring heads

Arbors and adaptors